


直柄麻花鑽頭

Straight Shank Twist Drills

D-101


◎適用於一般鋼料，HRC 30以下之合金鋼、鑄鐵、鑄鋼等被切削材。

◎適合一般鑽床、車床、桌上車床之鑽孔加工。

◎Suitable for drilling General Steels, Alloy Steels with hardness under HRC 30, Cast Iron and Cast Steel, etc.

◎Suitable for drilling operations on drilling machines, lathes and bench lathes.

直徑 D mm	全長 L mm	溝長 l mm
0.2	19	3
0.3	20	3.5
0.4	24	5.5
0.5	27	7.5
0.6	30	8.5
0.7	32	10
0.8	34	11
0.85	36	13
0.9	36	13
0.95	40	18
1.0	40	18
1.05	42	20
1.1	42	20
1.15	42	20
1.2	42	20
1.25	45	22
1.3	45	22
1.35	48	23
1.4	48	23
1.45	48	23
1.5	48	23
1.55	50	25
1.6	50	25
1.65	50	25
1.7	50	25
1.75	52	28
1.8	52	28
1.85	52	28
1.9	52	28
1.95	52	28
2.0	55	29
2.05	55	29
2.1	55	29
2.2	58	33
2.3	58	33
2.4	61	35
2.5	61	35
2.55	64	37
2.6	64	37
2.7	64	37

直徑 D mm	全長 L mm	溝長 l mm
2.8	67	39
2.9	71	42
3.0	71	42
3.05	71	42
3.1	71	42
3.2	71	42
3.3	73	45
3.4	73	45
3.5	73	45
3.55	76	48
3.6	76	48
3.7	76	48
3.8	76	48
3.9	79	51
4.0	83	54
4.1	83	54
4.2	83	54
4.3	83	54
4.4	86	56
4.5	86	56
4.55	86	56
4.6	86	56
4.7	89	59
4.8	89	59
4.9	92	62
5.0	92	62
5.05	92	62
5.1	92	62
5.2	95	64
5.3	95	64
5.4	95	64
5.5	95	64
5.6	98	67
5.7	98	67
5.8	98	67
5.9	98	67
6.0	102	70
6.1	102	70
6.2	102	70
6.3	102	70

直徑 D mm	全長 L mm	溝長 l mm
6.4	105	73
6.5	105	73
6.6	105	73
6.7	105	73
6.8	105	73
6.9	105	73
7.0	105	73
7.1	108	75
7.2	108	75
7.3	108	75
7.4	111	78
7.5	111	78
7.6	111	78
7.7	114	81
7.8	114	81
7.9	114	81
8.0	114	81
8.1	117	84
8.2	117	84
8.3	117	84
8.4	121	87
8.5	121	87
8.6	121	87
8.7	121	87
8.8	124	89
8.9	124	89
9.0	124	89
9.1	124	89
9.2	127	92
9.3	127	92
9.4	127	92
9.5	127	92
9.6	130	95
9.7	130	95
9.8	130	95
9.9	130	95
10.0	130	95
10.1	133	98
10.2	133	98
10.3	133	98

直徑 D mm	全長 L mm	溝長 l mm
10.4	133	98
10.5	137	100
10.6	137	100
10.7	137	100
10.8	140	103
10.9	140	103
11.0	140	103
11.1	140	103
11.2	143	106
11.3	143	106
11.4	143	106
11.5	143	106
11.6	146	109
11.7	146	109
11.8	146	109
11.9	146	109
12.0	149	111
12.1	149	111
12.2	149	111
12.3	149	111
12.4	152	114
12.5	152	114
12.6	152	114
12.7	152	114
12.8	152	114
12.9	152	114
13.0	152	114
13.5	160	108
14.0	160	108
14.5	169	114
15.0	169	114
15.5	178	120
16.0	178	120
16.5	184	125
17.0	184	125
17.5	191	130
18.0	191	130
18.5	198	135
19.0	198	135
19.5	205	140
20.0	205	140


切削條件請參照P43~46
Cutting data P43~46

直柄麻花鑽頭

Straight Shank Twist Drills

SUS

D-101



直徑 D in	全長 L mm	溝長 l mm
1/16	48	23
5/64	52	28
3/32	58	33
7/64	67	39
1/8	71	42
9/64	73	45
5/32	79	51
11/64	83	54
3/16	89	59
13/64	92	62

直徑 D in	全長 L mm	溝長 l mm
7/32	95	64
15/64	98	67
1/4	102	70
17/64	105	73
9/32	108	75
19/64	111	78
5/16	114	81
21/64	117	84
11/32	121	87
23/64	124	89

直徑 D in	全長 L mm	溝長 l mm
3/8	127	92
25/64	130	95
13/32	133	98
27/64	137	100
7/16	140	103
29/64	143	106
15/32	146	109
31/64	149	111
1/2	152	114

切削條件請參照P43~46
Cutting data P43~46